

The Quill Falcon Cyclone 120 Trailer is both convenient and powerful. It comprises of a Quill Falcon Cyclone 120, a 115 litre water tank and a 177cfm compressor providing customers with everything they need to start blasting almost immediately.

The Quill Falcon Cyclone 120 Trailer is extremely popular with many of our highways customers who are often working in difficult and remote locations where access to a water supply is often limited.

The Quill Falcon Cyclone 120 Trailer takes away the hassle and worry of being held up on site waiting for plant hire companies to deliver compressors and of potentially unreliable water supplies.



DIMENSIONS

 Capacity:
 121 litres

 Height:
 1750mm

 Width:
 1800mm

 Depth:
 4300mm

 Unladen Weight:
 1580kg

 Laden Weight:
 1920kg (garnet)

BLAST MEDIA

Number of 25kg bags to fill vesselGarnet:8 bagsIron Silicate:7 bagsGlass:5 bags

SPECIFICATIONS

Water Tank: 115 litre:

Water Consumption:100 - 200 ml per minuteGrit Type:Standard particle blast mediaGrit Consumption:0.4 - 0.7kg per minute

Grit Refill: Up to 8 hrs between refills

 Air Supply:
 177cfm

 Air Supply Hose:
 2 inch

 Blast Hose Size:
 1 inch

 Blast Hose Max Length:
 100m

 Blasting Pressure:
 20 – 120psi

Compressor Fuel Tank: 50 litres

Weights and dimensions are based on current models in manufacture. Cyclone Trailer System laden weight = full vessel of girlt and water and full tank of diesel. Consumption rates based on average dosing settings. Water consumption taken from water used at nozzle. Up to 1 litre of water per minute will be required to keep vessel pressurised. Girlt and water consumption may vary according to size of compressor, dosing valve setting, size of nozzle and type of blast media used.