

## The Quill Falcon Cyclone 60 is possibly the most versatile of the Quill Falcon Systems as it is powerful, easily portable and blasts for up to 3 hours before it requires refilling.

The Quill Falcon Cyclone 60 is popular with the offshore industry where it is flown across the globe to carry out surface preparation on helipads, completions and oil and gas tubulars, spot repairs for maintenance programmes and coating removal as part of NDT preparation. The Quill Falcon Cyclone 60 System is also widely used by the shipping industry during voyages to carry out maintenance work as ships transport cargo around the worlds waters.



## **DIMENSIONS**

 Capacity:
 58 litres

 Height:
 1070mm

 Width:
 620mm

 Depth:
 730mm

 Unladen Weight:
 138kg

 Laden Weight:
 269kg (garnet)

## **BLAST MEDIA**

Number of 25kg bags to fill vesselGarnet:4 bagsIron Silicate:3 bagsGlass:2 bags

## **SPECIFICATIONS**

Water Pressure & Flow:

Water Consumption:

Grit Type:

Standard pressure & flow

100 – 150ml per minute

Standard particle blast media

Grit Consumption:

0.6 – 1kg per minute

Grit Refill:

Up to 3 hrs between refills

Air Supply:

90 to 250cfm

Air Supply Hose:

3/4 inch or 2 inch

Blast Hose Size:1 inchBlast Hose Max Length:100mBlasting Pressure:20 - 100 psi

Weights and dimensions are based on current models in manufacture. Consumption rates based on average dosing settings. Water consumption taken from water used at nozzle. Up to 1 litre of water per minute will be required to keep vessel pressurised. Grit and water consumption may vary according to size of compressor, dosing valve setting, size of nozzle and type of blast media used.