



COMPRESSORS

- Proven reliability
- Compact and light weight
- Low emission zone compliant (under 37kW)
- Easy to operate
- Large fuel tank
- Water separator and after cooler (177cfm only)
- Refinery equipment (inlet shut down valve and spark arrestor) available on request



TECHNICAL DATA	90CFM	140CFM	177CFM
MAX WORKING PRESSURE	8.6 BAR (125PSI)	8.6 BAR (125PSI)	8.6 BAR (125PSI)
MAX FREE AIR DELIVERY	2.5M ³ /MIN (90CFM)	4M ³ /MIN (140CFM)	5M ³ /MIN (177CFM)
FUEL TANK CAPACITY	50 LITRES	40 LITRES	60 LITRES
FUEL CONSUMPTION (FULL)	5.4 LITRES/HOUR	8 LITRES/HOUR	10 LITRES/HOUR
NOISE LEVEL	84DB/98DB	84DB/98DB	84DB/98DB
LENGTH	2697MM	2999MM	3380MM
WIDTH	1390MM	1390MM	1430MM
HEIGHT	1235MM	1235MM	1290MM
WEIGHT	745KG	800KG	1100KG

Weights and dimensions are based on current models in manufacture.

For more information please call +44 (0) 1332 864664 or email sales@quillinternational.com
Quill International Group, Castle Lane, Melbourne, Derbyshire, DE73 8JB (UK)